

3005050028

Marine Master Clock 70000

123378-01 Marine Master Clock 70000



DESCRIPTION

- Accuracy +/- 0.1 sec./24 hours
- Wide range of different slave clocks (digital, 65, Ex-proof)
- Easy cabling and calibration
- Accessories and options like radio or satellite
- Signal receivers, RS232C/RS485 interface
- · Alarm outputs, etc.
- Automatic summer-winter time change-over
- LAN connection (70000L)

Marine Master Clock is the ideal solution for distribution of both Local and UTC time on board ships. The Master Clock is equipped with several outputs and inputs for control of Slave Clocks as well as distribution of time to computers and other equipment needing the correct time. The four Slave Clock outputs can be individually programmed for different types of clocks. External radio receivers / time synchronisation sources can be connected when higher accuracy is needed.

The clock is also used for the control and regulation of various energy consumers such as electrical striking plates and buzzers for pause signalling. The master Clock has a built-in yearly programmer with two relay outputs.

The Master Clock is equipped with 10 buttons and a 2 x 16 character LCD. To facilitate the change of time zones, two of the buttons are dedicated to this purpose. A light dimmer makes it possible to adjust the background-illumination to the surrounding light level.

Created: 29.07.2014, updated: 08.05.2020

page 1/4

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Zenitel products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.


SPECIFICATIONS

GENERAL

Crystal frequency	T4,915200 MHz	
Accuracy	0,1 sek./24 hours (+20C°)	
Microprocessor	HD6412394	
Time memory	30 days (Back-up with Super Capacitor)	
Impulse memory	72 hours	
Ambient temperature	0° C to +50°C	
Relative humidity	Max. 85% non-condensing	
Case	19" case according to drawing 084477-00, material aluminium. H=3U	
IP class	IP-20	
Weight	5.6 kg	
CE-approval, EMC	Emission according to EN61000-6-3, Immunity according to EN61000-6-2	
Supply voltage	90-264VAC 50/60Hz (Standard) / 24V DC	
ORDER NUMBER	DESCRIPTION	SHIP WEIGHT
3005050028	70000 Marine Master Clock	5.6 kg
	70000 Marine Master Clock	5.6 kg
Optional equipment:	70000 Marine Master Clock 70000L Marine Master Clock with network time server	5.6 kg 5.6 kg
Optional equipment: 3005050029		•
3005050028 Optional equipment: 3005050029 3005050031 Slave clocks	70000L Marine Master Clock with network time server	5.6 kg
Optional equipment: 3005050029 3005050031	70000L Marine Master Clock with network time server 70100 GPS receiver for master clock	5.6 kg
Optional equipment: 3005050029 3005050031	70000L Marine Master Clock with network time server 70100 GPS receiver for master clock	5.6 kg

Created: 29.07.2014, updated: 08.05.2020

page 2/4



Note: Ethernet port 2 to be used for Type 123378-11 o.no.3005050029

Created: 29.07.2014, updated: 08.05.2020

page 3/4

ACCESSORIES



122980-60 GPS RECEIVER

Item Number: 3005050031

Created: 29.07.2014, updated: 08.05.2020

page 4/4